PROGRAM-CONTROLLED UNIT

5   Cross-Reference to Related Application:

This application is a continuation of copending International

Application No. PCT/DE99/01988, filed July 1, 1999, which

designated the United States.

10 Background of the Invention:

    Field of the Invention:

The invention lies in the computer technology field and

pertains, more specifically, to a program-controlled unit with

one or more application-specifically configurable, intelligent

15 interfaces.

Program-controlled units are devices controlled by software

programs, that is to say microprocessors, microcontrollers or

the like. They exist in a multiplicity of diverse embodiments

20 and need not be described in specific detail.

Even though microprocessors, microcontrollers and the like can

be obtained in a wide variety of embodiments (or perhaps

precisely because of this), it is difficult or sometimes even

25 impossible to find one type which can satisfy the requirements

imposed in the specific individual case (and as far as possible only these requirements).

This is particularly applicable to microcontrollers because
5   after all, if possible, all the peripherals (analog/digital converter, digital/analog converter, timer, interrupt controller, etc.) required for the relevant application are intended to be integrated in the microcontrollers.

10 If the microcontroller selected for the relevant application is one which - for whatever reason - cannot satisfy all of the requirements imposed, then this generally means that the hardware within which the microcontroller is intended to be used becomes more complex. This turns out to be particularly
15 difficult and complex in the case of microcontrollers because the latter are not designed to cooperate with coprocessors and the like.

On the other hand, if the microcontroller selected for the
20 relevant application is one which can do more than is required, then the price of the product containing the microcontroller generally rises as a result. Added to this is the fact that often the operation of the microcontroller also becomes more complex and more complicated. This is because the
25 unrequired peripheral units of the microcontroller also have to be taken into account during the system development and be

controlled as intended by the intelligent core of the

microcontroller (the so-called microprocessor core or µP core)

which processes the instructions to be executed.

5   Summary of the Invention:

It is accordingly an object of the invention to provide a

program-controlled unit, which overcomes the above-mentioned

disadvantages of the heretofore-known devices and methods of

this general type and which provides for a program-controlled

10   unit that can be used optimally in each case for a large

number of highly varied applications.

With the foregoing and other objects in view there is

provided, in accordance with the invention, a program-

15   controlled unit with one or more application-specifically

configurable intelligent interfaces, comprising:

an intelligent core configured to process instructions to be

executed;

a plurality of units selected from the group consisting of

20   internal peripheral units disposed inside the program-

controlled unit, external peripheral units exterior to the

program-controlled unit, and one or more memory devices;

a structurable hardware unit selectively forming an

application-specifically configurable intelligent interface

for respectively connecting the intelligent core and the

units, including an interface connection between the

intelligent core and the internal peripheral units, between

the intelligent core and the external peripheral units,

5   between the intelligent core and the memory devices, and

between the plurality of units; and

wherein the structurable hardware unit is configured to

evaluate and process data and/or signals received thereby.

10   Alternatively, or in addition, the structurable hardware unit

is configured to inject instructions into an instruction

pipeline of the intelligent core.

In another alternative, or in addition, the structurable

15   hardware unit is configured to generate and to output

interrupt requests and/or event-signaling messages.

Finally, in a further alternative, the structurable hardware

unit is configured to selectively react to interrupt requests

20   or other event-signaling messages from devices connected

thereto and prevent the interrupt requests or the event-

signaling messages from being forwarded.

In sum, the program-controlled unit comprises one or more

25   application-specifically configurable intelligent interfaces.

Given appropriate configuration, such interfaces can to the greatest possible extent independently ensure that the intelligent core and one or more peripheral units and/or the intelligent core and one or more memory devices and/or two or more peripheral units themselves and/or one or more peripheral units and one or more memory devices cooperate as desired with minimal loading of the intelligent core.

In accordance with an added feature of the invention, the structurable hardware unit is disposed in circuit terms between the intelligent core and the plurality of units.

In accordance with an additional feature of the invention, the structurable hardware unit is connected to a multiplicity of potential data and signal sources and data and signal destinations, and a plurality of multiplexers are connected to the structurable hardware unit for selecting current data and signal sources and current data and signal destinations.

In accordance with another feature of the invention, the data and signal sources and the data and signal destinations comprise the intelligent core, the peripheral units, the memory devices, and/or portions of the structurable hardware unit itself.

In accordance with a further feature of the invention, the structuring of the structurable hardware unit selectively results in an alteration of given data paths and/or in a configuration of logic elements.

5

In accordance with again an added feature of the invention, the structurable hardware unit comprises a clock generation unit generating a clock signal and a logic block unit connected to receive the clock signal, the logic block unit

10 enabling devices to be connected via the structurable hardware unit to cooperate as desired.

In accordance with again an additional feature of the invention, the clock generation unit and the logic block unit

15 each contain configurable elements.

In accordance with again another feature of the invention, the clock generation unit is formed at least in part by a DNF logic configuration, a NAND array, a multiplexer-based logic

20 variant, and/or a structurable logic configuration.

In accordance with again a further feature of the invention, the logic block unit is formed at least in part by a DNF logic configuration, a NAND array, a multiplexer-based logic

25 variant, and/or a structurable logic configuration.

In accordance with yet an added feature of the invention, the logic block unit comprises at least one logic block subdivided at least partly into individually configurable sub-blocks with predetermined tasks. Preferably, one of the sub-blocks is

5   configured as a processing device enabled for arithmetic and/or logical processing of data input to the sub-block. It is also possible for one of the sub-blocks to be configured as a state machine for central sequence control. Similarly, one of the sub-blocks may be configured as an address calculation

10   device for calculating source and destination addresses. Also, it is possible for one of the sub-blocks to be configured as an instruction injection device for injecting instructions into the instruction pipeline of the intelligent core.

15   In accordance with yet an additional feature of the invention, the structurable hardware unit is configurable with fuses and/or anti-fuses.

       In accordance with yet another feature of the invention, the

20   structurable hardware unit is reversibly configurable. In a preferred embodiment, the structurable hardware unit is configurable based on data representing a desired configuration, and the data are stored in memory devices insertible into a memory or I/O area which is addressable by

25   the intelligent core.

In accordance with yet a further feature of the invention, the structurable hardware unit is enabled for reconfiguration only at predetermined times.

5   In accordance with a concomitant feature of the invention, the structurable hardware unit is enabled for reconfiguration at any time.

If the interfaces are made in such a way that they are
10 reconfigurable during entirely normal operation of the program-controlled unit, then the program-controlled unit can even be reconfigured dynamically.

Consequently, a program-controlled unit has been created which
15 can be used optimally in each case for a large number of highly varied applications.

Other features which are considered as characteristic for the invention are set forth in the appended claims.
20
Although the invention is illustrated and described herein as embodied in a program-controlled unit, it is nevertheless not intended to be limited to the details shown, since various modifications and structural changes may be made therein
25 without departing from the spirit of the invention and within the scope and range of equivalents of the claims.

The construction and method of operation of the invention,

however, together with additional objects and advantages

thereof will be best understood from the following description

5   of specific embodiments when read in connection with the

accompanying drawings.

Brief Description of the Drawings:

Fig. 1 is a schematic illustration of the construction of the

10   program-controlled unit according to the invention;

Fig. 2 is a schematic illustration of the construction of an

SLE layer 12 of the program-controlled unit in accordance with

Fig. 1;

15

Fig. 3 is a schematic diagram of the construction of a clock

generation unit 121 of the SLE layer 12 in accordance with

Fig. 2;

20   Fig. 4 is a schematic diagram of the construction of a logic

block unit 122 of the SLE layer 12 in accordance with Fig. 2;

and

Fig. 5 is a schematic diagram illustrating the configuration

25   of the logic block unit 122 in accordance with Fig. 4 for a

practical example.

Description of the Preferred Embodiments:

The exemplary program-controlled unit described in more detail

below is a microcontroller. It will be understood, however,

5   that the program-controlled unit can, in principle, also be

any other program-controlled unit, such as a microprocessor

for example.

The microcontroller considered herein is designated by the

10   reference symbol 1 in the figures. It is distinguished by the

fact that it comprises one or more application-specifically

configurable intelligent interfaces.

The novel microcontroller construction is referred to below as

15   application-specifically structurable controller architecture

or ASSC architecture.

The general structure of a microcontroller having the ASSC

architecture is schematically illustrated in Fig. 1.

20

Referring now to the figures of the drawing in detail and

first, particularly, to Fig. 1 thereof, there is shown an

intelligent core 11, which is usually referred to as

microprocessor core or µP core and processes the instructions

25   to be executed, a so-called SLE layer 12 and also peripheral

units 13 to 19, the peripheral units, for their part,

comprising a serial interface unit 13, a parallel interface unit 14, an analog/digital converter 15, a digital/analog converter 16, a timer 17, an interrupt controller 18 and, if appropriate, further peripheral units 19. Furthermore, an

5   external random access memory (RAM) 2 and an external read-only memory (ROM) 3 are provided; the RAM 2 and the ROM 3 can also be realized as internal memories without any difficulty.

The SLE layer 12 is arranged in circuit terms between the μP

10   core 11, peripheral units (for example the peripheral units 13 to 19) provided inside and/or outside the program-controlled unit, and/or memory devices (for example the RAM 2 and/or the ROM 3). It contains structurable data paths and/or logic elements which can be structured or configured in such a way

15   that the SLE layer 12 can be used as the at least one application-specifically configurable interface, more precisely as a configurable intelligent interface between the μP core and one or more peripheral units and/or between the μP core and one or more memory devices and/or between two or more

20   peripheral units themselves and/or between one or more peripheral units and one or more memory devices.

Within the SLE layer 12 there are preferably both direct connections and configurable data paths and data path linkages

25   between the devices which are connected or can be connected

-11-

via the SLE layer; the effect achieved by the direct connections is that the novel microcontroller can also be utilized like a conventional microcontroller (not having an SLE layer 12).

5

If the SLE layer 12 has access to memory devices (for example to the RAM 2 and/or to the ROM 3) it can transfer data from and to the memory devices independently, i.e. without the participation of the μP core, for itself and/or the μP core and/or the peripheral units. As a result, data transfers can be carried out more rapidly and without burdening the μP core 11. In this case, the SLE layer 12 is designed in such a way that it can identify and handle contending accesses to memory devices.

The SLE layer 12 can also be constructed without an interface to the memory devices present. In that case, the SLE layer and the μP core are preferably designed in such a way that the SLE layer can inject into the μP core (more precisely into the instruction pipeline thereof) instructions which can cause the μP core to carry out data transfers required by the SLE layer and/or the peripheral units.

The basic construction of the SLE layer 12 is illustrated in Fig. 2. The SLE layer 12 comprises a clock generation unit 121 and a logic block unit 122.

5 The clock generation unit 121 serves for supplying the logic block unit 122 with one or more different clock signals OUTCLK generated on the basis of one or more master clock signals INCLK. By way of example, clock signals having an altered frequency, altered duty ratio and/or altered phase angle

10 relative to the master clock signal or signals INCLK are generated in the clock generation unit 121.

In the example considered, the clock generation unit 121 comprises a fast configurable logic arrangement, for example a

15 so-called DNF logic arrangement (NOT-AND-OR logic), suitable for the practical realization of a disjunctive normal form, with downstream configurable storage, inversion/buffering and feedback. A two-stage DNF architecture (having two DNF blocks) is used in the example considered.

20

The fundamental construction of a clock generation unit 121 which generates an output clock signal OUTCLK on the basis of a master clock signal INCLK (for example the CPU clock signal) is illustrated in Fig. 3. The customary form of representation

25 for PALs (programmable array logic) and GALs (Generic array logic) has been chosen; transparent nodes represent

configurable connections, and filled-in (black) nodes

represent permanent connections.

In the example considered, the clock generation unit 121

5   comprises two identically constructed DNF blocks DNF1 and

DNF2, the first DNF block DNF1 representing a first DNF logic

stage and comprising AND elements A1, an OR element O1, a

flip-flop FF1 (clocked by the master clock signal), and a

multiplexer MUX1, and the second DNF block DNF2 representing a

10   second DNF logic stage and comprising AND elements A2, an OR

element O2, a flip-flop FF2 (clocked by the master clock

signal), and a multiplexer MUX2. The two DNF blocks DNF1 and

DNF2 are supplied with the same input signals. In the example

considered, the input signals comprise the master clock signal

15   INCLK, the inverted master clock signal /INCLK, an output

signal OUT1 of the first DNF block DNF1, the inverse output

signal /OUT1, an output signal OUT2 of the second DNF block

DNF2, and the inverse output signal /OUT2. The output signal

OUT2 of the second DNF block DNF2 and the inverse output

20   signal /OUT2 are fed to a multiplexer MUX3, and the output

signal thereof is output via a driver T2 as the output clock

signal OUTCLK to be generated.

The input signals, more precisely signal combinations which

25   can be selected via configurable connections, applied to the

respective DNF blocks DNF1 and DNF2 are applied to the AND

-14-

elements A1 and A2 of the respective DNF blocks. The output

signals of the AND elements A1 and A2 are fed to the OR

elements O1 and O2, respectively, or used as a reset signal

ASR for asynchronously resetting the flip-flops FF1 and FF2,

5 respectively. The output signals of the OR elements O1 and O2

are used as input signals of the flip-flops FF1 and FF2,

respectively; they (the output signals of the OR elements O1

and O2) and the inverse output signals are additionally

applied to the multiplexers MUX1 and MUX2, respectively. The

10 output signals and the inverse output signals of the flip-

flops FF1 and FF2 are likewise applied as input signals to the

multiplexers MUX1 and MUX2, respectively. The output signal

and the inverse output signal of the multiplexers MUX1 and

MUX2 are the output signals OUT1, /OUT1, OUT2 and /OUT2,

15 already mentioned above, of the two DNF blocks of the clock

generation unit 121.

Such a construction, or a similar construction, of the clock

generation unit 121 allows the generation of a multiplicity of

20 clock variations; the feedback of (internal) signals (the

signals OUT1, /OUT1, OUT2, /OUT2 in the example considered)

generated within the clock generation unit 121 also makes it

possible to realize non-binary duty and division ratios.

25 The arrangement shown in Fig. 3 is only a simple example for

explaining the fundamental construction of the clock

generation unit 121. In practice, the number of clock signals generated by the clock generation unit 121 should not be less than four. The lower limit for the possible number of terms per DNF should likewise be four. For each generated clock

5 signal, at least one internal signal should be generated and be provided like the internal signals OUT1, /OUT1, OUT2 and /OUT2, for example, as a possible basis for the clock signal generation.

10 The clock generation unit 121 need not necessarily be constructed using a two-stage DNF logic arrangement. The DNF logic arrangement used may also have fewer stages (that is to say just one stage) or arbitrarily many more stages.

15 Instead of the DNF logic arrangement, it is also possible to use another structurable logic arrangement, for example NAND arrays or multiplexer-based variants.

The logic block unit 122 already mentioned above is the actual

20 core of the SLE layer 12. Like the clock generation unit 121, it may comprise a structurable logic arrangement suitable for the practical realization of the disjunctive normal form, or one of the alternatives mentioned. Virtually any desired linkages, processing and evaluations of the input signals can

25 be carried out by means of such universally usable

structurable logic arrangements. A logic block unit 122 of
this type is extremely flexible.

In the example considered in the present case, the logic block

5   unit 122 has been realized differently: it contains one or
more logic blocks which are subdivided at least partly into
sub-blocks with predetermined tasks. This simplifies the
complexity of the gates used but hardly reduces the
flexibility of the SLE layer 12 – at any rate given a suitable

10   definition of the sub-blocks and corresponding cross-
connections between the individual sub-blocks.

The fundamental construction of a logic block subdivided into
various sub-blocks is illustrated in Fig. 4. The logic block

15   shown therein comprises four sub-blocks, namely

- a first sub-block 5 for the inputting and/or outputting of
  data and/or signals and the processing thereof,

20 - a second sub-block 6 for central sequence control for the
  operations proceeding within the relevant logic block,

- a third sub-block 7 for address calculations, and

25 - a fourth sub-block 8 for instruction injections into the µP.

In the example considered, the sub-blocks comprise

configurable multiplexers (for switching data paths as

desired), registers (for buffer-storing data and/or coded

5   states) and structurable logic (for linking data and/or

signals with one another and with constants and for coding and

decoding states).

In the example considered, the first sub-block 5 serves for

10   linking input data and/or signals with one another or with

constants; in the example considered, it comprises a first

multiplexer 51, a second multiplexer 52, a constant register

53, a first structurable logic arrangement 54, a second

structurable logic arrangement 55, and a register 56.

15

Data and/or signals switched through by the first multiplexer

51 are linked with one another or with constants stored in the

constant register 53 by the structurable logic arrangements 54

and 55 and output via the second multiplexer 52. The register

20   56 provided between the structurable logic arrangements 54 and

55 serves as a buffer store which can be used, for example,

for buffer-storing data that are to be linked until the other

data with which they are to be linked are valid; the data

and/or signals output by the structurable logic arrangement 54

25   can alternatively be transmitted via a bypass directly

(without a detour via the register 56) to the structurable

logic arrangement 55.

The multiplexers 51 (source selection) and 52 (destination

5   selection) connect the first sub-block 5 to different data

and/or signal sources and data and/or signal destinations.

Data and/or signal sources and data and/or signal destinations

are, in particular, the other sub-blocks, the µP core 11,

peripheral units (e.g. the peripheral units 13 to 19) provided

10 inside and/or outside the microcontroller, and/or memories

(e.g. the RAM 2 and/or the ROM 3). The connection to the

aforementioned or other data and/or signal sources and data

and/or signal destinations can be effected via databuses (but

does not have to be).

15

The first sub-block 5 is operatively comparable with the

arithmetic logic unit (ALU) of a program-controlled unit

working according to the Von Neumann Principle.

20 In the example considered, the second sub-block is a state

machine for central sequence control in the relevant logic

block; in the example considered, it comprises a first

structurable logic arrangement 61, a second structurable logic

arrangement 62, a register 63, and a multiplexer 64.

25

It is incumbent upon the structurable logic arrangement 61 to
determine the respective state of the relevant logic block, in
particular in a manner dependent on the states, signals and
signal profiles in or from the clock generation unit 121, the

5   other sub-blocks, the μP core 11, the peripheral units (e.g.
the peripheral units 13 to 19) and/or the memories (e.g. the
RAM 2 and/or the ROM 3); the operation which should (must)
currently proceed in the logic block depends on the respective
state of said logic block. The aforesaid state, more precisely

10 a data value representing it, may be stored in the register 63
and be decoded as required by the structurable logic
arrangement 62. The structurable logic arrangement 62 outputs
one or more output signals. These output signals are control
signals based on the respective state of the relevant logic

15 block and are output via the multiplexer 64 in particular to
the other sub-blocks, but also, if appropriate, to the μP
core, the peripheral units and/or the memory devices.

In the example considered, the second sub-block 6 can be used

20 to realize different simple automata types (up to Mealy), to
be precise also with different clocks.

The task incumbent upon the second sub-block 6 is comparable
with the control unit of a Von Neumann CPU, the processing of

instructions naturally being omitted (the states are traversed in a manner triggered by external signals).

In the example considered, the third sub-block 7 serves in particular (but not exclusively) for address calculation for block-by-block data transfers; in the example considered, it comprises an address register 71, a constant register 72, an incrementing/decrementing unit 73, a first structurable logic arrangement 74 and a second structurable logic arrangement 75.

The third sub-block 7 can calculate source and destination addresses and output them to the other sub-blocks, the µP core, the peripheral units and/or the memory.

The present address in each case is stored in the address register 71 and can be incremented or decremented by the incrementing/decrementing unit 73. The constant register 72 is designed to store an end address, and an address comparison can be carried out by the structurable logic arrangements (in order, for example, to be able to check whether the address stored in the address register 71 has reached the end address stored in the constant register 72).

The provision of this third sub-block 7 is optional and is very useful in particular (but not exclusively) when the SLE layer 12 has direct access to the memory.

In the example considered, the fourth sub-block 8 serves for injecting instructions into the pipeline of the µP core 11; in the example considered, it comprises a constant register 81

5 and a structurable logic arrangement 82.

Instructions are injected under the control of the second sub-block 6, more precisely the control signals output by the latter. The instruction code of the instruction to be injected

10 is stored in the constant register 81 and is communicated as required (if appropriate together with address and data information) via the structurable logic arrangement 82 to the µP core 11; for this purpose, the second sub-block 6 puts the structurable logic arrangement 82, as required, into a state

15 in which the instruction code stored in the constant register 81 (if appropriate together with the data output from the first sub-block 5 and/or the address output from the third sub-block 7) is injected into the pipeline of the µP core.

20 As has already been mentioned or indicated at least in part above, there are diverse cross-connections between the individual sub-blocks 5 to 8. The cross-connections depicted in Fig. 4 are to be regarded only as examples. The number of cross-connections and the beginning and end points thereof

25 depend in particular on the concrete application of the

relevant logic block and the number and function of the sub-blocks thereof and may be designed, as required, as configurable connections.

5 The at least partial division of the logic blocks of the logic block unit 122 of the SLE layer 12 into sub-blocks enables the practical realization of the logic blocks with minimal complexity. In particular, considerably fewer linkage possibilities have to be provided compared with the
10 realization of the logic block unit using one or more structurable logic arrangements which can be used universally; the reason for this is that because each sub-block only has to perform one precisely defined task, the sub-blocks in each case have to be able to link only a few signals with one
15 another – in contrast to structurable logic arrangements which can be used universally.

The tasks which have to be performed by the respective sub-blocks, and the cross-connections between the individual sub-
20 blocks make it possible for the relevant logic blocks to have similar performance to that of logic blocks constructed using structurable logic arrangements which can be used universally.

This holds true even when the logic blocks are divided into
25 sub-blocks which are constructed differently and/or have to perform different tasks and/or have different cross-

connections and/or are provided in a larger or smaller number
than the sub-blocks 5 to 8 which are used in the example
considered in the present case and are described with
reference to Fig. 4.

5

In the case of data group operations, it may be necessary to
additionally integrate memory units into the SLE layer 12. In
that case, results required for later calculations do not have
to be swapped into storage devices provided outside the SLE
10   layer 12, but rather can be immediately (buffer-) stored
internally within the SLE layer 12.

In the example considered, the structurable logic arrangements
used in the sub-blocks are DNF logic arrangements whose
15   construction essentially corresponds to the construction of
the DNF logic arrangements used in the clock generation unit
121; in this case, the input and output signals are not, of
course, clock signals but rather data and/or control signals,
and required clock signals (for example for clocking the flip-
20   flops) are selected from the clock signals generated by the
clock generation unit 121.

However, there is no restriction to the effect that the
structurable logic arrangements of the logic block 122 are
25   such or similar DNF logic arrangements; instead, it is also

possible to use NAND arrays, multiplexer-based variants or other structurable logic arrangements.

The configuration of the configurable elements of the SLE

5 layer, i.e. the configuration of the multiplexers, the configurable connections within the structurable logic arrangements and the registers can essentially be effected like the configuration of the known field-programmable logic arrangements (PLAs, GALs, PLDs, FPGAs etc.).

10

A first possibility in this respect consists in the (irreversible) production or erasure of connections using so-called fuses or antifuses.

Another possibility consists in carrying out reversible

15

configuration based on data representing the desired configuration, the data being stored in EPROMS, EEPROMS or the like provided inside or outside the program-controlled unit. As a result, the configuration of the program-controlled unit

20 can be changed a limited number of times.

A further possibility consists in carrying out reversible configuration based on data representing the desired configuration, but where the data are stored in a RAM or the

25 like. As a result, the configuration of the program-controlled

unit can be changed an unlimited number of times and very

rapidly.

The EPROMs, EEPROMS, RAMs or other memories in which the data

5   representing the configuration of the program-controlled unit

are stored are preferably designed in such a way that they can

be inserted into the memory or I/O area which can be accessed

by the µP core 11. The configuration of the SLE layer 12 can

then be set as desired by the µP core 11 itself.

10

If the intention is to preclude the situation where the

operation of the program-controlled unit is disturbed by the

configuration of the SLE layer 12, provision may be made for

allowing the configuration only at predetermined points in

15   time (for example within a predetermined time after the

resetting of the program-controlled unit).

Given appropriate configuration of the SLE layer 12, the

latter can be assigned specific tasks which, heretofore, could

20   or had to be processed exclusively or to a very great extent

by the µP core 11. These tasks include in particular (but not

exclusively) the preprocessing, postprocessing, evaluation

and/or control of data and/or signals and also the initiation

and monitoring of the cooperation of the devices connected via

25   the SLE layer 12.

If the configuration or a reconfiguration of the SLE layer 12 is permitted at any time, then these tasks can even be swapped dynamically into the SLE layer.

5

Irrespective of this, that is say even when dynamic configuration of the SLE layer 12 is not possible, the loading on the μP core 11 can be considerably relieved by the SLE layer 12. This is explained below using a practical example.

10

The example relates to analog/digital conversion of data. More precisely, suppose that

- an A/D converter (for example the A/D converter 15) having a conversion width of 8 bits is started by a timer (for example by the timer 17),

15

- the result of the A/D conversion is stored together with a 12-bit counting marker,

20

- the result of the A/D conversion is monitored in respect of specific limit values being exceeded and undershot, in which case branching to a specific routine should be effected when the limit values are exceeded or undershot,

25

▪ and the operation is terminated after 2048 measurements.

An application of this type requires a relatively high

complexity in the case of a purely software-based solution.

5 Since a typical A/D converter integrated in a microcontroller

does not yield the result spontaneously, that is to say works

as a so-called flash converter and has a conversion time in

the region of a few microseconds, one of the following paths

must be taken in connection with the exact execution of the

10 application specification:

1) The timer triggers an interrupt. The interrupt service

routine starts the A/D conversion and is then ended. The

A/D converter likewise triggers an interrupt when the

15 conversion is ended. The interrupt service routine that is

thereupon executed causes the A/D conversion result to be

read out and processed.

2) The timer triggers an interrupt. In the interrupt service

20 routine that is thereupon executed, the A/D conversion is

started, there is a wait for the end of the conversion, and

finally (after the end of the conversion) the A/D

conversion result is read out and processed.

25 If the conversion times are shorter than the interrupt latency

times, the second variant should be preferred. Otherwise, the

first variant would be preferable. In general, however, the

third variant below is the most favorable:

3)   The timer triggers an interrupt. In the interrupt service

5   routine that is thereupon executed, the last A/D

conversion result is read out, the next A/D conversion is

started, and the A/D conversion result that has been read

out is evaluated.

10   In this third variant, although the A/D conversion result is

generally read and evaluated later than would actually be

possible, this delay is generally tolerable.

The complexity that has to be implemented for practical

15   realization of the third variant is undoubtedly the least.

Nevertheless the processing of the interrupt service routine

whose execution is initiated by the timer interrupt lasts at

least (i.e. if one instruction is executed per clock cycle and

if there are no instances of the limit values being exceeded

20   or undershot by the A/D conversion results, and if there were

not interrupt latency times) 30 clock cycles.

If the execution of this application is shifted as far as

possible into the SLE layer 12, then it can be carried out

25   considerably faster.

The logic block which is shown in Fig. 4 and described with reference thereto should then be configured, for example, in such a way that the structure shown in Fig. 5 is produced.

5   The input signals of the arrangement shown in Fig. 5 are the A/D conversion results of the A/D converter 15, which are designated by ad[0..7], and also the pulses of the timer 17, which are designated by Start_T.

10   The structurable elements of the logic block in accordance with Fig. 5 are conFig.d in such a way that said logic block, in the event of the limit values being exceeded or undershot by the A/D conversion results and when the end of the measurement series is reached, sends interrupt requests

15   designated by Irq_Con and, for the purpose of storing the A/D conversion results together with the counting marker, injects corresponding instructions into the instruction pipeline of the µP core. In this case, it is incumbent

20   ▪ upon the second sub-block 6 to effect central sequence control within the relevant logic block,

▪ upon the first sub-block 5 to effect comparison of the A/D conversion data ad[0..7] received from the A/D converter 15

25   with values u[0..7] (upper limit value) and l[0..7] (lower

limit value) stored in the constant register 53, and to

effect generation of the interrupt requests Irq_Con,

5 ■ upon the third sub-block 7 to effect comparison of addresses
(for the purpose of completing the instructions to be
injected and for the purpose of determining the end of the
measurement series), and

10 ■ upon the fourth sub-block 8 to effect generation and/or
compilation and injection of the instructions to be
injected.

In this case, the structurable logic arrangements 61 and 62
are configured in such a way that they generate output signals
15 Irq_Gen, Inject_1, Inject_2, New_Adr and Read on the basis of
input signals MClk, Start_T, End_Of_Adr and Reset using
internal signals S0, S1, S2 and End_Reached, as defined by the
Boolean equations below:

20 In the structurable logic arrangement 61:

S0 = /S2 * /S0 * Start_T * /End_Reached +

/S2 * S1 * /S0 * /End_Reached;

S1 = /S2 * /S1 * S0 * /End_Reached +

25 /S2 * S1 * /S0 * /End_Reached;

S2 = /S2 * S1 * S0;

```
S0.CLK = MClk;              /* Clocking with MClk */

S1.CLK = MClk;              /* Clocking with MClk */

S2.CLK = MClk;              /* Clocking with MClk */

/* This describes the pass through 5 states, triggered by

Start_T */


End_Reached = End_Of_Adr + End_Reached * /Reset;

End_Reached.CLK = MClk;        /* Clocking with MClk */

/* Stored End-Flag */
```

In the structurable logic arrangement 62:

```
New_Adr = /S2 * S1 * /S0 + /S2 * S1 * S0;

/* Signal for state 2 and 3 */


Inject_1 = /S2 * S1 * /S0;

/* Injection 1. Move instruction */


Inject_2 = /S2 * S1 * S0;

/* Injection 2. Move instruction */


Read = /S2 * /S1 * S0;

/* Triggering of the read operation */


Irq_Gen = End_Reached;

/* Triggering interrupt request at end */
```

The structurable logic arrangements 54 and 55 are configured
in such a way that they generate output signals Irq_Con1,
Irq_Con2, b_ad[0..7] on the basis of input signals ad[0..7],

5   u[0..7], 1[0..7], Read, Irq_Gen using internal signals
tmp_upper [0..3], tmp_lower[0..3], tmp_eq[0..3] (for
intermediate results), tmp_ad[0..7] (for buffer-storage after
interrogation) and Irq_Tmp1 (for IRQ generation and resetting)
as defined by the Boolean equations below:

10

In the structurable logic arrangement 54:

```
        tmp_upper[z]  = /u[2z+1] * ad[2z+1] +

                         u[2z+1] * ad[2z+1] * /u[2z] * ad[2z] +

                         u[2z+1] * ad[2z+1] * /u[2z] * ad[2z];

15      tmp_lower[z]  =  1[2z+1] * /ad[2z+1] +

                         1[2z+1] * /ad[2z+1] 1[2z] * /ad[2z]

                        /1[2z+1] * /ad[2z+1] 1[2z] * /ad[2z];

        tmp_eq[z]     =  u[2z+1] * ad[2z+1] * u[2z] * ad[2z..+

20                       u[2z+1] * ad[2z+1] * /u[2z] * ad[2z] +

                        /u[2z+1] * ad[2z+1] * u[2z] * ad[2z..+

                        /u[2z+1] * /ad[2z+1] * /u[2z] * /ad[2z];
```

        /* z runs from 0 to 3, comparison for larger/smaller and

25   equality */

```
     tmp_upper[z].CLK = /Read; /* clocking at read-out end */

     tmp_lower[z].CLK = /Read; /* clocking at read-out end */

     tmp_eq[z].CLK = /Read; /* clocking at read-out end */


5    tmp_ad[x] = ad[x]         /* x from 0 .. 7 */

     tmp_ad[x].CLK = /Read;    /* clocking at read-out end */


     Irq_Tmp1 = 1;

     Irq_Tmp1.CLK = Irq_Gen;  /* clocking with Irq_Gen */

10   Irq_Tmp1.AR = Irq1Reset; /* reset with Irq1Reset */

     /* Generating IRQ for take-up end */


In the structurable logic arrangement 55:


15   Irq_Con1 = Irq_Tmp1;

     /* IRQ is generated for take-up end */


     Irq_Con2 =        tmp_upper[3] + tmp_tmp[3] * tmp_upper[2] +

                       tmp_eq[3] * tmp_eq[2] * tmp_upper[1] +

20                     tmp_eq[3] + tmp_eq[2] * tmp_eq[1] *

                                           tmp_upper[0] +

                       /* Overflow */

                       tmp_lower[3] + tmp_eq[3] * tmp_lower[2] +

                       tmp_eq[3] * tmp_eq[2] * tmp_lower[1] +

25                     tmp_eq[3] * tmp_eq[2] * tmp_eq[1] *

                                           tmp_lower[0];
```

-34-

/* Underflow */

b_ad[y] tmp_ad[y]   /* y runs from 0 .. 7 */

The structurable logic arrangements 74 and 75 are configured

5   in such a way that they generate output signals End_Adr and

BA[0..15] on the basis of input signals A[0..15], EA[0..15]

using internal signals temp[0..7] as defined by the Boolean

equations below:

10   In the structural logic arrangement 74:

temp[x] = /A[2x] * /EA[2x] * /A[2x+1] * /EA[2x+1] +

A[2x] * /EA[2x] * /A[2x+1] * /EA[2x+1] +

A[2x] * /EA[2x] * A[2x+1] * EA[2x+1] +

15   A[2x] * EA[2x] * A[2x+1] * EA[2x+1];

/* x runs from 0 to 7, comparison for equality */

In the structurable logic arrangement 75:

20   End_Adr = temp[0] * temp[1] * temp[2] * temp[3] *

temp[4] * temp[5] * temp[6] * temp[7];

/* produces 1 if addresses and comparison address

identical */

25   BA[y] = A[y];   /* y runs from 0 .. 15 */

The structurable logic arrangement 82 is configured in such a way that it generates output signals Inject and MP[0..31] (assuming 32-bit interface to the µP core) on the basis of input signals Inject_1, Inject_2, BA[0..15], b_ad[0..7], and

5   CR4[0..15] and defined by the Boolean equations below:

    Inject = Inject_1 + Inject_2;

    MP[0..15] =   CR4[0..15] * Inject_1 +

                    CR4[0..15] * Inject_2;

10 /* the 16-bit instruction code stored */

    /* in CR4[0..15] is communicated */

    MP[16..23] =   BA[0..7] * Inject_1 +

                    b_ad[0..7] * Inject_2;

    MP[24..31] =   BA[8..15] * Inject_1;

15 /* the operand or operands */

    /* (16-bit address or 8-bit AD value) */

    /* are communicated */

As is apparent from the explanations above, each time A/D

20 conversion data from the A/D converter are read out and processed, the arrangement in accordance with Fig. 5 passes through four states, namely:

1) Reading of the A/D conversion result ad[0..7] from the A/D

25   converter with automatic restart of the A/D converter.

-36-

2) The A/D conversion result is processed, i.e. the A/D

conversion result is compared with an upper limit value

u[0..7] stored in the constant memory 53 and a lower limit

value l[0..7] likewise stored in the constant memory. At

5   the same time, a first move instruction is injected into

the pipeline of the μP core.

3) A second move instruction is injected. This instruction

comprises a transfer of the A/D conversion result to the

10   address that has been incremented in the meantime. If the

A/D conversion result lies outside the range defined by the

limit values, an interrupt request is simultaneously

triggered.

15 4) The end of the 2048 conversions is possibly reached. In

this case, a flag is set which prevents further reading-out

and processing of A/D conversion results. Furthermore, a

further interrupt request is triggered for the purpose of

signaling the end of the routine.

20

If it assumed that each state requires precisely one sequence

clock signal, then 4 clock signals are required for each

instance of reading out and processing A/D conversion data

from the A/D converter; the μP core is temporarily burdened by

two or three CPU clock cycles through the injected
instructions.

With incorporation of the SLE layer 12, the reading and

5   evaluation of A/D conversion results considered in the present
case can be carried out in a small fraction of the time which
would be necessary if the procedure were as it has been
heretofore, that is to say if the complete sequence control
and data processing were essentially left exclusively to the

10   µP core 11.

It goes without saying that similar advantages can also be
obtained in conjunction with completely different applications
from the example described above.

15

As a result, the program-controlled unit described can be used
optimally in each case for a large number of highly varied
applications.